


PROJECT NAME:	_CATALOG NUMBER:
NOTEC:	FIVELIDE COLIEDLILE.

Page: 1 of 2

## **LED 8" COMMERCIAL RECESSED** RETROFIT DOWNLIGHT

**ECONOMIC SERIES** 













#### PRODUCT DESCRIPTION:

The ENERGY STAR qualified eight-inch ECO Series LED Recessed Retrofit Downlight combines low up-front cost, minimal labor, best-in-class energy efficiency, and architectural-quality light to deliver an exceptional value for customers.

The ECO Series retrofit offers out-of-the-box dimming compatibility using 0-10-volt controls and features a one-piece design that is quick and easy to install into existing recessed frames.

#### **FEATURES:**

- Universal voltage (120-277)
- · Mounts into existing recessed frame
- Supplied with optional retaining clips if existing frame does not have adequate friction springs to secure reflector
- cULus listed for damp location use
- CRI: 84
- PF: >.9
- Dimmable to 10%
- Five year limited warranty

#### **CONSTRUCTIONS:**

- Supplied with an aluminum reflector in a haze finish
- External driver for easy retrofit and maintenance
- Power supply features integral thermal protection

MODEL SELECTION (Full list of order codes on pg. 2)  Typical order example: RRECO82330W						
RRECO	8			w		
FAMILY	SIZE	WATTAGE (NOMIAL)	сст	TRIM		
RRECO= Commercial Recessed Retrofit Downlight Economic Series	<b>8=</b> 8"	23= 23W 40= 40W	<b>30=</b> 3000K <b>40=</b> 4000K	<b>W=</b> White		



# LED COMMERCIAL RECESSED **RETROFIT DOWNLIGHT**

**ECONOMIC SERIES** 

Page: 2 of 2

SPECIFICATIONS:		RRECO82330W	RRECO82340W	RRECO84030W	RRECO84040W	
ITEM	SPECIFICATION	DETAILS				
	Power Consumption (W)	22.4	21.9	37.0	38.6	
	Lumens Delivered (Im)	1,680	1,690	3,100	3,300	
	Efficacy (Im/W)	75	77	85	85	
GENERAL PERFORMANCE	CRI	≥80				
	Color Temperature (K)	3000K	4000K	3000K	4000K	
	L70 Lifetime (hours)	50,000				
	Color Consistency	Proprietary binning for uniform color				
ELECTRICAL	Power Factor	0.99				
	Input Voltage	120-277V				
	Compatible Dimmers	Designed to be compatible with any 0-10v dimmer				
PHYSICAL	Weight	2 lbs				
	Mounting	Mounts into existing recessed frame				
	Operating Temperature	-4°F to 104°F				
	Humidity	20-85% RH, non-condensing				
CERTIFICATION	Certification	cULus, LM-79, Energy Star, FCC				
	Material Usage	RoHS compliant; no mercury				
	Environment	Indoor				
	Warranty	5 years				

### **ORDERING\*:**

ORDER CODE	MODEL	ССТ	WATTAGE	
96864	RRECO82330W	3000K	22	
96867	RRECO82340W	4000K	23	
95374	RRECO84030W	3000K	40	
95375	RRECO84040W	4000K	40	

<sup>\*</sup>Please contact your MaxLite representative to order products that don't have order codes listed here. (Additional CCT available, contact MaxLite for info.)

