

34197 - Remote 2ft LED Glass Tubes T5 HE Tubes

LED9T5/G2/835HE

- ☞ Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time. Each LED tube is operated by a GE Lightechâ„¢ driver. See reverse for LED tubes and Lightech driver product details.
- ☞ UL Listed
- ☞ Required Driver
- ☞ 66% longer life than LFL (50 000 vs. 30 000 hours)
- ☞ Check ballast compatibility at www.gelighting.com/LEDTUBES-ballast-compatibility

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Description	LED_Bs_G5
Base Type	G5
Dimmable	No
Product Technology	LED
Rated Life (Hours)	50000 h
Dimmable / Non-Dimmable	No
Lamp Count	1
Life in Years	0 yr
Requested Structure	Carton
Estimated Energy Cost per Year	1.08
Bulb Shape	T5

PHOTOMETRIC CHARACTERISTICS

Nominal Initial Lumen per Watt	77
Initial Lumens-nominal	1150 lm
Color Rendering Index-CRI	80
Color Temperature	3500 K

PRODUCT INFORMATION

Product Code	34197
Description	LED9T5/G2/835HE
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168341974
Standard Package GTIN	00043168341974
No Of Items Per Sales Unit	
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	
Alternative Unit Of Measure	CASE
Standard Package Quantity	20
Ean UPC	043168341974
Standard Package GTIN	10043168341971
No Of Items Per Sales Unit	
No Of Items Per Standard Package	20
Sales Unit	Case
UCC	

DIMENSIONS

Bulb Max Overall Length-MOL	22.5 in
-----------------------------	---------

ELECTRICAL CHARACTERISTICS

Rated power (Watts)	15 W
---------------------	------