

32133 - Ballast Bypass 2ft

LED8BT8/G2/840

- ☞ Existing fixture is wired to bypass the ballast.
- ☞ Fast and easy LED upgrade.
- ☞ Low energy LFL replacement.
- ☞ 66% longer life than LFL (50 000 vs. 30 000 hours)
- ☞ Better quality of light "instant on."
- ☞ Fully illuminates fixture - >270° light distribution.
- ☞ Easy disposal non-hazardous waste.
- ☞ Additional Cost Savings- ballast bypass wiring eliminates ballast replacement costs.
- ☞ For In-Line Fuse & Socket Kits please check our Awaken brochure.

PRODUCT PHOTO



GENERAL CHARACTERISTICS

| | |
|--------------------------------|------------|
| Base Description | LED_Bs_G13 |
| Base Type | G13 |
| Dimmable | No |
| Product Technology | LED |
| Rated Life (Hours) | 50000 h |
| Dimmable / Non-Dimmable | No |
| Lamp Count | 1 |
| Life in Years | 45.7 yr |
| Requested Structure | Carton |
| Estimated Energy Cost per Year | 0.96 |
| Bulb Shape | T8 |

PHOTOMETRIC CHARACTERISTICS

| | |
|--------------------------------|---------|
| Nominal Initial Lumen per Watt | 125 |
| Initial Lumens-nominal | 1000 lm |
| Color Rendering Index-CRI | 80 |
| Color Temperature | 4000 K |

PRODUCT INFORMATION

| | |
|----------------------------------|----------------|
| Product Code | 32133 |
| Description | LED8BT8/G2/840 |
| Alternative Unit Of Measure | CASE |
| Standard Package Quantity | 20 |
| Ean UPC | 043168321334 |
| Standard Package GTIN | 10043168321331 |
| No Of Items Per Sales Unit | |
| No Of Items Per Standard Package | 20 |
| Sales Unit | Case |
| UCC | |
| Alternative Unit Of Measure | EACH |
| Standard Package Quantity | 1 |
| Ean UPC | 043168321334 |
| Standard Package GTIN | 00043168321334 |
| No Of Items Per Sales Unit | |
| No Of Items Per Standard Package | 1 |
| Sales Unit | Each |
| UCC | |

DIMENSIONS

| | |
|-----------------------------|---------|
| Bulb Max Overall Length-MOL | 24.0 in |
|-----------------------------|---------|

ELECTRICAL CHARACTERISTICS

| | |
|---------------------|-------|
| Voltage <Nom> | 120 V |
| Rated power (Watts) | 8 W |