

100WR 200WR 300WR

Wrap Around



Features

Housing

Die-formed Cold-rolled Steel

Optical

Shade: Prismatic Acrylic

Electrical

Lamp

Integrated Linear LED Module or DLC Listed T8 LED Tube

Certification

UL/cUL, ETL/cETL Listed



Integrated LED Strips Type

Model	Input Voltage	Input Wattage	Lumen (TYP)	LED CT	CRI	Dimension (L X W X H)	DLC
200WRD1-36W-xxxxK	120V ~ 277V	38W	3600	4000K	>80	49.5" x 8.8" x 2.5"	Yes
300WRD1-50W-xxxxK	120V ~ 277V	50W	5000	4000K	>80	49.0" x 11.2" x 2.5"	---
300WRD1-72W-xxxxK	120V ~ 277V	72W	7200	4000K	>80	49.0" x 11.2" x 2.5"	---

Color Temperature Option: 4000K or 5000K

Bi-Level Dimming with Built-in Sensor

Model	Input Voltage	Input Wattage	Lumen (TYP)	LED CT	CRI	Dimension (L X W X H)
200WRD1-BI	120V ~ 277V	36W	3600	3000K	80	49.5" x 8.8" x 2.5"

Built-in Emergency Battery Back Up Type

Model	Input Voltage	Input Wattage	Lumen (TYP)	LED CT / CRI	Dimension (L X W X H)
200WRD1-EM	120V ~ 277V	36W	3600	3000K / 80	49.5" x 8.8" x 2.5"

100WR 200WR 300WR

Wrap Around



DLC Listed T8 LED Tube Type

Model	Input Voltage	Input Wattage	T8 LED Tube	Lumen (TYP)	LED CT/CRI	Dimension (L X W X H)
100WRD-36W	120V ~ 277V	36W	2 x 18W	4400	4000K or 5000K / > 80	49.0" x 6.5" x 2.5"
200WRD-36W	120V ~ 277V	36W	2 x 18W	4400	4000K or 5000K / > 80	49.5" x 8.8" x 2.5"
300WRD-72W	120V ~ 277V	72W	4 x 18W	8800	4000K or 5000K / > 80	49.0" x 11.2" x 2.5"

Color Temperature Option: 3000K, 4000K or 5000K

T8 Lamp Type

Model	Input Voltage	Input Wattage	Power Factor	Lamp	Dimension (L X W X H)
100WR HPF	120V ~ 277V	58W	>0.98	2 x F32T8, 32W	49.0" x 6.5" x 2.5"
200WR HPF	120V ~ 277V	58W	>0.98	2 x F32T8, 32W	49.5" x 8.8" x 2.5"
300WR HPF	120V ~ 277V	106W	>0.98	4 x F32T8, 32W	49.0" x 11.2" x 2.5"