# **MDF036**

# Wall Sconce



## **Features**

## Housing

Die-formed Cold-rolled Steel

Finish Option: -62 Satin Nickel -30 Oil Rubbed Bronze

#### Optical

Shade: High Transmission Glass Creates Excellent Light Distribution and Uniformity LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

### **Electrical**

High Power Factor, Low THD

### Lamp

LED Type: Integrate LED Module, 3000K LED

More Color Temperature Option 3500K, 4000K, 5000K

GU24 Type: - CFL Bulb, 2700K or 4000K


- 9W LED Bulb, 3000K or 4000K

### Certification

UL/cUL or ETL/cETL Listed, Suitable for Damp Locations

#### Warranty

5 Years Limited Warranty on Driver and LED





# **LED Type**

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Finish/Shade	Dimension (W x H x D)	Energy Star
MDF036D-xxxxK	120V-277V	22W	3000K	>80	1850	Satin Nickel / Frosted Glass	12.0" x 12.0" x 4.0"	Yes

### **GU24 Type**

Model	Input Voltage	Lamp	Finish	Shade	Dimension (W x H x D)	Energy Star
MDF036PG-213	120V	2 x 13W GU24	Satin Nickel	Frosted Glass	12.0" x 12.0" x 4.0"	

Sunpark Electronics Corp. 16200 S. Figueroa St., Gardena, CA90248 www.sunparkelecronics.com Phone: (310) 324-8880 Fax: (310) 324-4020 Specifications are subject to change without notice.

2/5/19 DS\_MDF036.docx