



SPECIFICATION FEATURE:



10W

15W

REPLACES 100W INCANDESCENT OR 26W CFL FIXTURE

PHILIPS 3030 LED LIGHT SOURCE WITH CLASS 2 UL LED DRIVER

BUILT WITH UV PROOF POLYCARBONATE COVER

INPUT VOLTAGE	110 - 277 VAC
CRI	>80
LUMEN PER WATT	100 LM/W
AVAILABLE CCT	3000K,5000K
LIFE SPAN	50,000 HOURS
OPERATION TEMPERATURE	-40°F ~ 104°F
LUMEN	990
MOUNTING OPTIONS	WALL MOUNT

INPUT VOLTAGE	110 - 277 VAC
CRI	>80
LUMEN PER WATT	100 LM/W
AVAILABLE CCT	3000K,5000K
LIFE SPAN	50,000 HOURS
OPERATION TEMPERATURE	-40°F ~ 104°F
LUMEN	1500
MOUNTING OPTIONS	WALL MOUNT



ORDERING OPTIONS:

EXAMPLE: LEDSWM 10W 50K 277V

10W - 15W

LEDSWM	10W	50K	[BLANK]	[BLANK]	[BLANK]
SERIES LEDSWM	RATED WATTAGE 10W 10 WATT 15W 15 WATT	COLOR TEMP 30K 3000 KELVIN 50K 5000 KELVIN	INPUT VOLTAGE BLANK 110 - 277 VAC	FINISHING BLANK DARK BRONZE WH WHITE NK NICKEL	OPTIONS -PC INTERNAL PHOTOCELL

4 to 6 week lead time for white and black finishing

DIMENSIONS:

