



Specifications

Efficacy	≥ 126 LM/W
Color	30K (50W), 35K, 40K, 50K
CRI	> 80
Input Voltage	110V-277V
Operating Temp.	-20°F-122°F
Power Factor	>0.90
Size	2x2: 22.52"L x 20.67"W x 2.6"H 2x4: 46.61"L x 20.67"W x 2.6"H
Weight	2x2 at 5.3lbs 2x4 at 10.8lbs
Dimming	0-10V dimmable
Warranty	7-year (10-year optional)

Ordering Information

Product #	Size	Wattage	Lumen	Color
AT-R4-15W-XDZ-35K	2x2	15W	2025	3500K
AT-R4-15W-XDZ-40K	2x2	15W	2025	4000K
AT-R4-15W-XDZ-50K	2x2	15W	2025	5000K
AT-R4-25W-XDZ-35K	2x2	25W	3300	3500K
AT-R4-25W-XDZ-40K	2x2	25W	3300	4000K
AT-R4-25W-XDZ-50K	2x2	25W	3300	5000K
AT-R4-36W-XDZ-35K	2x2	36W	5000	3500K
AT-R4-36W-XDZ-40K	2x2	36W	5000	4000K
AT-R4-36W-XDZ-50K	2x2	36W	5000	5000K
AT-R7-25W-XDZ-35K	2x4	25W	3375	3500K
AT-R7-25W-XDZ-40K	2x4	25W	3375	4000K
AT-R7-25W-XDZ-50K	2x4	25W	3375	5000K
AT-R7-36W-XDZ-35K	2x4	36W	5000	3500K
AT-R7-36W-XDZ-40K	2x4	36W	5000	4000K
AT-R7-36W-XDZ-50K	2x4	36W	5000	5000K

Features

- Easy installation, no screw needed
- 0-10V Dimmable
- Certified for utility rebate
- Microwave sensor optional

Product Compliance & Certifications:

- UL
- DLC 4.2 Premium

Description

Aleddra's EasiFit® Troffer Retrofit Kit is an energy-efficient and cost-effective replacement for an existing linear troffer luminaire. It fits into the existing troffer housing, saving the labor of removing it and the trouble of disposing it. It also provides a more aesthetic appearance than the old fixture. The 0-10V dimming makes it controllable by the daylighting harvest system for further energy savings.

The EasiFit® Troffer Kit is UL/DLC certified for utility rebate.

Photos

