STANDARD OUTDOOR STYLE PROTECTOR™



1230BPX120



930CPX120

- **Secondary circuit ground fault protection**, *interrupting transformer output to eliminate the danger of a fire in case of an arc to ground.*
- **LED diagnostics**, *reduces troubleshooting time*.
- **Same dimension as all UL506 models**, *which means there is no need to redesign casings, raceways or existing signs in order to take advantage of a more reliable and safer transformer.*
- **A 29-minute by-pass switch**, *which enables efficient fault detection, in the same manner that you were accustomed to work with old UL506 transformers.*
- **Three automatic resets**, *eliminating nuisance tripping, providing continuous and better performance, thus saving service costs.*
- **Available in 277 and 347V**, *which results in potential cost savings, as you can install more transformers per circuit when compared to 120V applications.*

Allanson
LIGHTING ELECTRICS

STANDARD OUTDOOR STYLE , HEAVY DUTY OUTDOOR NON-WEATHERPROOF
NORMAL POWER FACTOR 120/277/347 VOLTS-60 HERTZ

DRAWING	120V		277V		347V		VA	SECONDARY kV-mA	WT lbs
	PART No.	LINE AMP	PART No.	LINE AMP	PART No.	LINE AMP			
A	1530BPX120	3.75	1530BPX277	1.62	1530BPX347	1.30	450	15 - 30	22
	1230BPX120	3.00	1230BPX277	1.30	1230BPX347	1.04	360	12 - 30	22
	1030BPX120	2.62	1030BPX277	1.14	1030BPX347	0.91	315	10.5 - 30	22
B	930CPX120	2.25	930CPX277	0.97	930CPX347	0.78	270	9 - 30	13
	7530CPX120	1.88	7530CPX277	0.81	7530CPX347	0.65	225	7.5 - 30	13
	630C120	1.50	630C277	0.65	630C347	0.52	180	6 - 30	13
	530C120	1.33	530C277	0.58	530C347	0.46	160	5 - 30	13
	430C120	1.17	430C277	0.51	430C347	0.40	140	4 - 30	13
	330C120	0.83	330C277	0.36	330C347	0.29	100	3 - 30	13
C	1560BPX120	7.50	1560BPX277	3.25	1560BPX347	2.60	900	15 - 60	36
	1260BPX120	6.00	1260BPX277	2.60	1260BPX347	2.08	720	12 - 60	35
A	960BPX120	4.50	960BPX277	1.95	960BPX347	1.57	540	9 - 60	22
	7560BPX120	3.75	7560BPX277	1.62	7560BPX347	1.30	450	7.5 - 60	22
	660BPX120	3.00	660BPX277	1.30	660BPX347	1.04	360	6 - 60	22
B	560CPX120	2.66	560CPX277	1.15	560CPX347	0.87	320	5 - 60	13
	460CPX120	2.40	460CPX277	1.04	460CPX347	0.69	290	4 - 60	13
	360CPX120	2.00	360CPX277	0.87	360CPX347	0.52	240	3 - 60	13


The above transformers are UL2161 Listed and CSA Approved

STANDARD OUTDOOR STYLE , HEAVY DUTY OUTDOOR NON-WEATHERPROOF
HIGH POWER FACTOR 120/277/347 VOLTS-60 HERTZ

DRAWING	120V		277V		347V		VA	SECONDARY kV-mA	WT lbs
	PART NO	LINE AMP	PART NO	LINE AMP	PART NO	LINE AMP			
D	P1530BPX120	2.08	P1530BPX277	0.90	P1530BPX347	0.72	250	15 - 30	23
	P1230BPX120	1.67	P1230BPX277	0.72	P1230BPX347	0.58	200	12 - 30	23
	P1030BPX120	1.46	P1030BPX277	0.63	P1030BPX347	0.50	170	10.5 - 30	23
E	P930CPX120	1.25	P930CPX277	0.54	P930CPX347	0.43	150	9 - 30	15
	P7530CPX120	1.04	P7530CPX277	0.45	P7530CPX347	0.36	125	7.5 - 30	15
	P630C120	0.83	P630C277	0.36	P630C347	0.29	100	6 - 30	15
	P530C120	0.75	P530C277	0.32	P530C347	0.26	90	5 - 30	15
	P430C120	0.62	P430C277	0.27	P430C347	0.22	75	4 - 30	15
	P330C120	0.46	P330C277	0.20	P330C347	0.16	55	3 - 30	15
C	P1560BPX120	4.17	P1560BPX277	1.81	P1560BPX347	1.44	500	15 - 60	36
	P1260BPX120	3.33	P1260BPX277	1.44	P1260BPX347	1.15	400	12 - 60	35
D	P960BPX120	2.50	P960BPX277	1.08	P960BPX347	0.86	300	9 - 60	23
	P7560BPX120	2.08	P7560BPX277	0.90	P7560BPX347	0.72	250	7.5 - 60	23
	P660BPX120	1.67	P660BPX277	0.72	P660BPX347	0.58	200	6 - 60	23
E	P560CPX120	1.42	P560CPX277	0.62	P560CPX347	0.49	170	5 - 60	15
	P460CPX120	1.09	P460CPX277	0.47	P460CPX347	0.38	130	4 - 60	15
	P360CPX120	0.85	P360CPX277	0.36	P360CPX347	0.29	100	3 - 60	15

The above transformers are UL2161 Listed and CSA Approved

Standard Outdoor Protector™ "BPX" Style



Drawing	Overall	L	W	H	ML	Mw
A	11	9	4 3/8	5 3/8	10	2 1/2
C	11 1/8	9 1/2	5 3/8	6 1/2	10 1/8	2 1/2
D	11 1/4	9	4 3/8	6 3/8	10 1/4	2 1/2

Please note that the dimensions are measured in inches.

Phone 1-800-661-7251 Fax 416-752-6717
33 Cranfield Road Toronto, ON M4B 3H2 Canada www.allanson.com