
Catalog Number	
Notes	
Type	

Contractor Select™

JSBC

JUNO SLIMBASICS™ LED SURFACE MOUNT DOWNLIGHT



Sleek, low-profile LED round surface mount downlights in 5" and 7" sizes. Provides economical installation by mounting directly over standard junction boxes. Provides general illumination in residential and commercial applications including multi-family and hospitality. Ideal for use in corridors, foyers, living spaces, closets, hallways, pantries, stairways and much more. Available in easy-to-carry 4-packs to reduce packaging waste. Packaging made from recyclable cardboard.

FEATURES:

- 4-Packs contain 4 fixtures and cannot be broken
- Available in 3000K color temperature
- Minimum 90 CRI

Catalog Number	UPC	Description	Lumens	Input Watts	CCT	CRI	Voltage	Finish	Pallet qty.
JSBC 5IN 30K 90CRI WH CP4 M4	193048341362	LED Surface Mount Downlight	650	11W	3000K	90	120V	White	450
JSBC 7IN 30K 90CRI WH CP4 M4	193048341393	LED Surface Mount Downlight	1050	17W	3000K	90	120V	White	450

Specifications

INTENDED USE:
Sleek, low-profile LED round surface mount downlights in 5" and 7" sizes • Provides economical installation by mounting directly over standard junction boxes • Provides general illumination in residential and commercial applications including multi-family and hospitality • Ideal for use in corridors, foyers, living spaces, closets, hallways, pantries, stairways and much more • Available in easy-to-carry 4-packs to reduce packaging waste • Packaging made from recyclable cardboard • 4-Packs contain 4 fixtures and cannot be broken

CONSTRUCTION:
Shallow, 1" low profile with metal housing and white finish • Metal backplate allows for solid installation to junction box.

ELECTRICAL:
Dedicated 120 volt (120) driver at 50/60Hz • Power factor > 0.9 at 120V input •120 volt driver is dimmable with the use of most incandescent, magnetic low voltage and electronic low voltage wall box dimmers.

JUNCTION BOX MOUNTING:
Fixture provided with leads for direct wire connection in j-box • Installs directly to industry standard junction boxes • Compatible boxes include 3" and 4" metal or plastic standard and fire rated round and octagon junction boxes • Compatible with pancake boxes if enough depth is allowed for connections and wiring space • Quick mount bracket provides easy twist turn locking of fully assembled fixture to junction box • Suitable for wall and ceiling mount • Suitable for use within closet storage spaces when installed per NEC requirements. Junction box sizes vary - Verify compatibility with fixture prior to installation

LISTINGS:
ENERGY STAR® certified product. • Certified to the high efficacy requirements of California T24 JA8-2016 • CSA listed for US and Canada


WARRANTY:
5-year limited warranty. Complete warranty terms located at:
www.acuitybrands.com/support/customer-support/terms-and-conditions

Note:All reports are based on published industry procedures; actual performance may differ as a result of the end-user environment and applications.
All values are design or typical values, measured under laboratory conditions at 25 °C.
Specifications subject to change without notice.


Dimensions

	Width	Depth
JSBC 5IN	5.25" (13.6)	1" (2.6)
JSBC 7IN	7.15" (18.2)	1" (2.6)

All dimensions are inches (centimeters) unless otherwise indicated.



JSBC 5IN



JSBC 7IN

© 2019-2020 Acuity Brands Lighting, Inc. All rights reserved. Rev. 04/13/20