LED DESIGNER SCONCE POWERED BY THE LEDSR G2

120-277V — VOLTAGE
0-10V DIM — DIMMING
130-150 LPW — EFFICACY (LIGHT ENGINE)
-20°C TO 60°C — OPERATING TEMP
<15% THD, >0.9 — PWR FACTOR/THD
EMG — OPTIONAL EMG BATTERY BACKUP
80+ — CRI
L70 >50,000 — RATED LIFE
10 YEAR WARRANTY — WARRANTY

future-proof elegant & flexible



powered by the LEDSR G2 light engine

- High transmission, acrylic plastic lens.
- Flexible: FlexWatt allows you to select between 4 wattages & FlexColor between 3 colors...all in the same fixture!
- Future-proof: Powered by easily replaceable & upgradeable LEDSR G2 light engine.
- Optional emergency battery back-up and control options.

flexWATT STANDARD

6W 9W 12W 15W

flexCOLOR STANDARD

- 3000°K WARM WHITE
- 3500°K SOFT WHITE
- 4000°K NEUTRAL WHITE

flexCONTROL OPTIONAL

ORDER CONTROL READY, BASIC CONTROL OR LG ADVANCED CONTROL

MODEL #	UPC	W	LUMENS	CCT (K)
RP-SCD-11N-8L-40K-WC-G2	844006022525	6W	816	4000K

ENERGY STAR · RoHS Compliant · ETL LISTED US UL 1598 LISTED FIXTURE · FC CLASS B


Light Efficient Design

LIGHT EFFICIENT DESIGN HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013
INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949
847.380.3540 • led-llc.com

07.01.20 Information is subject to change without notice.

LED DESIGNER SCONCE POWERED BY THE LEDSR G2

LED DESIGNER SCONCE



PART NUMBER BUILDER

MFR	PRODUCT	SIZE	LUMENS	COLOR	FUNCTION	GEN	OPTIONS
RP	SCD	11			WC	G2	
		N = INCHES	8L 14L 17L 21L	30K = 3000K, 85CRI 35K = 3500K, 85CRI 40K = 4000K, 85CRI	WC= FlexWatt + FlexColor		OC1=high/low motion sensor EMG=90min emergency battery backup LVD=works on either 120V or 277V

ORDERING EXAMPLE

RP-SCD-11N-8L-30K-WC-G2

Default lumen package (wattage and CCT) are shown below in bold. There are two ways to achieve a non-default lumen package and/or CCT:
1. You can easily adjust in field via our FlexWatt* and FlexColor internal switches. **2**. Have us adjust the FlexWatt* and FlexColor at the factory for an additional charge.
* LVD option removes FlexWatt, must specify lumen output when ordering LVD.

CASE QTY	QUICK SHIP	ENERGY STAR	DEFAULT PART #	UPC	DESCRIPTION	WATTAGE	LUMENS	LPW	CCT (K)
1	•	•	RP-SCD-11N-8L-40K-WC-G2	844006022525	11IN DESIGNER SCONCE	**6**/10/12/15	780-2130	130-142	3000/3500/**4000**
1	•		RP-SCD-11N-8L-40K-WC-G2 -OC1	844006023614	11IN DESIGNER SCONCE	**6**/10/12/15	780-2130	130-142	3000/3500/**4000**

EFFICIENCY/ELECTRICAL DATA

	CCT SELECTION		
LUMEN SELECTION	830	835	840
8L	780LM, 6W	780LM, 6W	816LM, 6W
14L	1370LM, 10W	1440LM, 10W	1370LM, 10W
17L	1692LM, 12W	1680LM, 12W	1764LM, 12W
21L	2025LM, 15W	2100LM, 15W	2130LM, 15W

Light Efficient Design

LIGHT EFFICIENT DESIGN HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013
INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949
847.380.3540 • led-llc.com

07.01.20 Information is subject to change without notice.