naturaled®

Turning Light into Savings



SB
Area Light / Shoebox
75W, 110W, 180W, 240W

naturaLED® Area Light constructed with durable, die-cast aluminum housing and excellent thermal design. Our SB series is perfect for parking lots, streets, walkways, and streetscape, providing you with uniform and consistant color. A wide range of wattage selections equal to 150 watt to 1,000 watt HID fixtures, reducing maintenance and saving lamp & ballast replacement costs.

Our fixtures are DLC certified and IP65 rated with 3 types of mounting options available: Swivel Bracket, Slip Fitter, and 6" Extruded Arm. Compatible Integrated automomous and photocell motion sensors are available as options to address your needs.

5 YEAR WARRANTY

Dimmable 0-10V

TYPE ANGLE 3

50,000 Rated Life Hours

Key Features & Benefits

- DesignLights Consortium Certified
- IP65
- Uniform and consistent color
- Aluminum die cast housing
- Excellent thermal design
- CRI:70
- Universal Voltage 120-277V
- Operating Temp: -22°F~122°F
- 50,000 Hours rated average life
- 0-10V dimming
- Motion sensor compatible
- Photocell sensor compatible

Applications

- Parking Lot Lighting
- Street Lighting
- Site Lighting
- Streetscape Lighting
- Area Lighting

3 Color Choices

Bronze Black White

Qualifications

IP65 outdoor rated · DLC · cULus · FC · LM 79 · LM 80 · RoHS COMPLIANT · Title 24

2000 S. Grove Ave, Bldg B, Ontario, CA 91761 | tel: 909-930-6868 fax: 909-930-9988 | www.mynaturaLED.com

© 2016 Plusrite®

ORDERING INFORMATION

Item Code	Description	Color Temp	Wattage	Lumen Output	Equivalent Wattage	Voltage (V)	CRI	Beam Angle	Mount	Color			
7112	LED-FXSB75/3S/40K/DB-SF	4000K	75	5,898	250	120-277	70	Type 3	Slip Fitter	Bronze	●	●	●
7113	LED-FXSB75/3S/40K/DB-SB	4000K	75	5,898	250	120-277	70	Type 3	Swivel	Bronze	●	●	●
7114	LED-FXSB75/3S/40K/DB-EA6	4000K	75	5,898	250	120-277	70	Type 3	6” Arm	Bronze	●	●	●
7115	LED-FXSB75/3S/50K/DB-SF	5000K	75	5,898	250	120-277	70	Type 3	Slip Fitter	Bronze	●	●	●
7116	LED-FXSB75/3S/50K/DB-SB	5000K	75	5,898	250	120-277	70	Type 3	Swivel	Bronze	●	●	●
7117	LED-FXSB75/3S/50K/DB-EA6	5000K	75	5,898	250	120-277	70	Type 3	6” Arm	Bronze	●	●	●
7118	LED-FXSB110/3S/40K/DB-SF	4000K	110	8,574	250-400	120-277	70	Type 3	Slip Fitter	Bronze	●	●	●
7119	LED-FXSB110/3S/40K/DB-SB	4000K	110	8,574	250-400	120-277	70	Type 3	Swivel	Bronze	●	●	●
7120	LED-FXSB110/3S/40K/DB-EA6	4000K	110	8,574	250-400	120-277	70	Type 3	6” Arm	Bronze	●	●	●
7121	LED-FXSB110/3S/50K/DB-SF	5000K	110	8,574	250-400	120-277	70	Type 3	Slip Fitter	Bronze	●	●	●
7122	LED-FXSB110/3S/50K/DB-SB	5000K	110	8,574	250-400	120-277	70	Type 3	Swivel	Bronze	●	●	●
7123	LED-FXSB110/3S/50K/DB-EA6	5000K	110	8,574	250-400	120-277	70	Type 3	6” Arm	Bronze	●	●	●
7176	LED-FXSB110/3S/50K/BK-EA6	5000K	110	8,574	250-400	120-277	70	Type 3	6” Arm	Black	●	●	●
7169	LED-FXSB110/3S/50K/WH-EA6	5000K	110	8,574	250-400	120-277	70	Type 3	6” Arm	White	●	●	●
7192	LED-FXSB180/3S/40K/DB-SF	4000K	180	19,073	400-750	120-277	70	Type 3	Slip Fitter	Bronze	●	●	●
7193	LED-FXSB180/3S/40K/DB-SB	4000K	180	19,073	400-750	120-277	70	Type 3	Swivel	Bronze	●	●	●
7194	LED-FXSB180/3S/40K/DB-EA6	4000K	180	19,073	400-750	120-277	70	Type 3	6” Arm	Bronze	●	●	●
7195	LED-FXSB180/3S/50K/DB-SF	5000K	180	21,194	400-750	120-277	70	Type 3	Slip Fitter	Bronze	●	●	●
7196	LED-FXSB180/3S/50K/DB-SB	5000K	180	21,194	400-750	120-277	70	Type 3	Swivel	Bronze	●	●	●
7197	LED-FXSB180/3S/50K/DB-EA6	5000K	180	21,194	400-750	120-277	70	Type 3	6” Arm	Bronze	●	●	●
7400	LED-FXSB240/3S/40K/DB-SF	4000K	240	24,010	750-1000	120-277	70	Type 3	Slip Fitter	Bronze	●	●	●
7401	LED-FXSB240/3S/40K/DB-SB	4000K	240	24,010	750-1000	120-277	70	Type 3	Swivel	Bronze	●	●	●
7402	LED-FXSB240/3S/40K/DB-EA6	4000K	240	24,010	750-1000	120-277	70	Type 3	6” Arm	Bronze	●	●	●
7403	LED-FXSB240/3S/50K/DB-SF	5000K	240	25,638	750-1000	120-277	70	Type 3	Slip Fitter	Bronze	●	●	●
7404	LED-FXSB240/3S/50K/DB-SB	5000K	240	25,638	750-1000	120-277	70	Type 3	Swivel	Bronze	●	●	●
7405	LED-FXSB240/3S/50K/DB-EA6	5000K	240	25,638	750-1000	120-277	70	Type 3	6” Arm	Bronze	●	●	●

Accessories

P10024	MT-SF/DB	Slip Fitter (Bronze)
P10025	MT-SB/DB	Swivel Bracket (Bronze)
P10026	MT-EA6/DB	6” Arm (Bronze)
P10046	MT-4PA/DB	4” Round Pole Adaptor (Bronze)
P10047	MT-5PA/DB	5” Round Pole Adaptor (Bronze)
P10048	MT-6PA/DB	6” Round Pole Adaptor (Bronze)
P10049	MT-4PA/WH	4” Round Pole Adaptor (White)
P10050	MT-5PA/WH	5” Round Pole Adaptor (White)
P10051	MT-6PA/WH	6” Round Pole Adaptor (White)
P10043	SEN-LOD-500-SPD	Motion/Photocell 0-10V /100-277V Recomemded for 8-20ft Height. Coverage: 2 x Height
P10045	SEN-LOD-500-SPC	Motion/Photocell 0-10V /100-277V Recomemded for 15-30ft Height. Coverage: 3 x Height




SEN-LOD-500-SPC
Height: 15-30ft
(3-Times Height Coverage)

IP66




SEN-LOD-500-SPD
Height: 8-20 ft
(2-Times Height Coverage)

Dimensions




Wattage	A	B	C	Weight
75	12.25-in	12.25-in	5.00-in	16.00-in
110	16.50-in	16.50-in	7.00-in	25.00-in




Wattage	A	B	C	Weight
180	21.30-in	17.29-in	5.51-in	30.00-in
240	21.30-in	20.72-in	5.51-in	37.00-in


Mounting Dimensions



a	b	c	d	e	f	g
5.5-in	0.50-in	2.50-in	0.50-in	0.25-in	3.75-in	4.75-in




a	b	c	d	e	f	g
7.00-in	6.50-in	3.00-in	3.50-in	0.50-in	--	--




a	b	c	d	e	f	g
8.75-in	4.00-in	4.50-in	2.50-in	4.00-in	2.00-in	2-M10


Illuminace Distribution


Shoebox Wattage: 75W







Shoebox Wattage: 110W







Shoebox Wattage: 180W





Shoebox Wattage: 240W





Master Carton Package

