

Project	
Schedule	Date
Notes	

DESCRIPTION

naturaLED® PAR LED bulb provides a superior replacement for all incandescent lamp applications. An energy efficient integrated LED driver deliver the same lumen output equivalent with up to 80% energy savings. Our LEDs are direct replacement with energy star certification. Perfect for display case lighting, track lighting, jewelry lighting and general lighting.



FEATURES

- Energy Star Certified
- For Damp Location
- CEC / JA8-2016
- Direct replacement and Instant on
- Up to 80% energy savings
- Contains no mercury or lead
- UL/cUL Listed
- Material: Polycarbonate
- Input Line Voltage: 120V
- CRI: 90
- Dimmable
- Powerfactor >0.9
- Beam Angle: Flood
- Operating temperature: -4°F ~ 104°F
- Rated 25,000 hours average life

APPLICATIONS

- Display Case Lighting
- Recessed Downlight
- Accent Lighting
- General Lighting
- Residential Lighting
- Restaurant Lighting

WARRANTY

- 5 Year Warranty

Ordering Information		EXAMPLE: LED9BR30/65L/927		
LED	9	BR30	65L	927
	Wattage	Style	Lumens	CRI/Color Temp
LED	9 9 Watts	BR30 BR30	65L 650 Lm	9 CRI90 27 2700K

ORDERING

Watts (W)	Ordering Code	Description	Color Temp (K)	Lumens (lm)	Equiv. Wattage (W)	Base	CRI	Bulb Shape	Rated Hrs	JA8	Energy Star
8	5834	LED8R20/50L/927	2700K	525	50	E26	90	R20	25,000	•	•
8	5982	LED8R20/52L/950	5000K	525	50	E26	90	R20	25,000	-	•
9	5835	LED9BR30/65L/927	2700K	650	65	E26	90	BR30	25,000	•	•
9	5983	LED9BR30/71L/950	5000K	715	65	E26	90	BR30	25,000	-	•
12	5842	LED12BR30/90L/927	2700K	938	75	E26	90	BR30	25,000	•	•
12	5893	LED12BR30/95L/930	3000K	950	75	E26	90	BR30	25,000	•	•
12	5978	LED12BR30/90L/940	4000K	950	75	E26	90	BR30	25,000	-	•
12	5984	LED12BR30/95L/950	5000K	950	75	E26	90	BR30	25,000	-	•
15	5836	LED15BR40/120L/927	2700K	1,200	85	E26	90	BR40	25,000	•	•

SPECIFICATIONS

R20	BR30	BR40
Weight: 2.24-oz	Weight: 5.60-oz	Weight: 9.12-oz

PACKAGE

R20
BR30

Package (Master)
20

BR40

Package (Master)
10