

LRS SERIES Outdoor Lighting

LRS-H-MCT-C90-MGBR


WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!



Customer Name: _____

Project Name: _____

Note: _____ Type: _____



6 3/4"(L) x 6 3/4"(W) x 4"(H)

LED Non-Cutoff Wall Pack with Photocell is ideal for general site lighting, loading docks, doorway, pathway and parking areas.

Features

- Back plate: Die-cast aluminum
- Polycarbonate Lens
- 5 Year Warranty
- Multi CCT Switch is Inside Fixture

Technical Specifications

Electrical:

- Voltage: 120V AC 60Hz
- Wattage: 12W
- Power Factor: >0.90
- Efficacy: 54 LPW

Mechanical:

- Back plate: Die-Cast Aluminum with Mounting/Gasket Installed
- Marine-Grade Bronze Finish,
- This Process Consists of:
 - Abrasive Blasting
 - Chemical Conversion Coat IAW TTC
 - Epoxy Primer and SDTGIC Polyester Top Coat With 200-Hour on Salt Spray Test
- Operating Temperature: -4°F to 104°F
- Wet Location
- 5 Year Warranty
- IP44

Lighting:

- Total Lumens: 650LM
- Color Temperatures: 3000K/ 4000K/ 5000K
- Color Rendering Index: CRI ≥ 90
- Beam Angle: 90° x 110°
- Rated life: 0,000 Hrs

Applications:

- Ideal for general site lighting, loading docks, doorway, pathway and parking areas.


Other Models:

- 12W | 650LM | LRS-H-MCT-C90-WH
- 12W | 650LM | LRS-H-MCT-C90-BK


Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com | www.westgatecontrols.co



Photometrics: LRS-H-MCT-C90-MGBR



BUD Rating: B0-U3-G1



Other Views:



Side View



Front View



Back View

Performance Table: LRS-H-MCT-C90-MGBR

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LRS-H-MCT-C90-MGBR	12W	120V	650LM	3000K 4000K 5000K	B0-U3-G1	54

Sample Ordering

Model	Color Temp.	CRI	Housing
LRS - H - MCT - C90 - MGBR			

Other Models:



LRS-H-MCT-C90-BR



LRS-H-MCT-C90-WH

