



A19 REPLACEMENT : HIGH-WATT

DESCRIPTION

LED High-Watt A-Lamps directly replace high-wattage incandescent A lamps at a fraction of the energy cost.

FEATURES

- Direct replacement for 125/150/200W incandescent A-lamps and up to 70W HID lamps
- 80% more efficient and 30x longer life than standard incandescent
- Shatter-resistant plastic housing for reduced risk of injury and breakage
- Non-dimmable
- Operates on universal 120-277V line voltage

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Restaurants & Hospitality
- Retail
- Residential
- Accent/Display Lighting
- Healthcare
- Bollards
- Post-Tops



PERFORMANCE	Power Consumption	19W	25W	29W
	Lumens	2,000	2,550	3,050
	Efficacy (LPW)	105	102	105
	CRI		80+	
	Beam		220°	
	CCT		3000K, 4000K, 5000K	
	Life (L70)		25,000 hours	
ELECTRICAL	Power Factor	>0.9		
	Input Voltage	120-277V		
CONSTRUCTION	Operating Temperature	-20°C (-4°F) to 45°C (113°F)		
	Base	E26		
LISTINGS	Certification(s)	ENERGY STAR® Rated; cULus Classified		
	Material Usage	RoHS Compliant; no mercury or lead		
	Environment	Enclosed fixture rated; UL Approved for damp locations		

PERFORMANCE SUMMARY

Order Code	Item #	Lumens	Watts	LPW	CCT	CRI	Volts	MOL	Life/Hours	Replaces Incan.	ES
10530	LED19WA21/OMN/830-G8	2,000	19W	105	3000K	80+	120-277V	5.55"	25,000	125W A21	
10531	LED19WA21/OMN/840-G8	2,000	19W	105	4000K	80+	120-277V	5.55"	25,000	125W A21	★
10532	LED19WA21/OMN/850-G8	2,000	19W	105	5000K	80+	120-277V	5.55"	25,000	125W A21	★
10533	LED25WA21/OMN/830-G8	2,550	25W	102	3000K	80+	120-277V	5.47"	25,000	150W A21	
10534	LED25WA21/OMN/840-G8	2,550	25W	102	4000K	80+	120-277V	5.47"	25,000	150W A21	★
10535	LED25WA21/OMN/850-G8	2,550	25W	102	5000K	80+	120-277V	5.47"	25,000	150W A21	
10536	LED29WA23/OMN/830-G8	3,050	29W	105	3000K	80+	120-277V	6.30"	25,000	200W A23	★
10537	LED29WA23/OMN/840-G8	3,050	29W	105	4000K	80+	120-277V	6.30"	25,000	200W A23	★
10538	LED29WA23/OMN/850-G8	3,050	29W	105	5000K	80+	120-277V	6.30"	25,000	200W A23	★

NOTE: Use order code when ordering. ★ENERGY STAR® Rated

DIMENSIONS

