

LED FILAMENT DECORATIVE

DESCRIPTION

LED Filament Decorative Replacement Lamps are a cost-effective, energy-efficient alternative to incandescent filament lamps.

FEATURES

- LED lamp with the same vintage look and feel as traditional incandescent filament lamps
- 80% more efficient and 20x longer life than incandescent
- 2200K amber and 2700K clear available in various decorative shapes
- Compatible with a wide array of leading edge TRIAC dimmers
- Suitable for use in totally enclosed fixtures
- Dimmable down to 10% of full light output
- Not intended for use with emergency exits

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Chandeliers
- Accent/display lighting
- Sconces
- Lanterns
- Hospitality
- Residential
- Vanity mirrors



Top: A15; A19; A19 Silver Bowl; ST19
 Middle: G16; G25; S14
 Bottom: B11 E26; B11 E12; BA11 E12; T10; T6 E12; T6.5 E17



| | | | | | | |
|---------------------|-------------------|-------------------------------------|-----------------|---------------------|-----|---------|
| PERFORMANCE | Power Consumption | 2.5W | 4W | 4.5W | 5W | 7W |
| | Lumens | 200/250 | 250/300/350/400 | 350/400/450/470/500 | 500 | 700/800 |
| | Efficacy (LPW) | 80/100 | 63/75/88/100 | 78/89/100/104/111 | 100 | 100/114 |
| | CRI | 80+ | | | | |
| | CCT | 2200K, 2700K | | | | |
| | Life (L70) | 15,000 hours | | | | |
| ELECTRICAL | Power Factor | ≥0.9 | | | | |
| | THD | <20% | | | | |
| | Input Voltage | 120VAC | | | | |
| CONSTRUCTION | Lens | Frosted | | | | |
| | Base | G5 | | | | |
| LISTINGS | Certification(s) | ENERGY STAR® Approved; cULus Listed | | | | |
| | Material Usage | RoHS Compliant; no mercury or lead | | | | |
| | Environment | Suitable for use in damp locations | | | | |

PERFORMANCE SUMMARY

| Order Code | Item # | Lumens | Watts | CCT | CRI | Volts | Shape | Base | MOL | MOD | Life/Hours | ES |
|------------|-------------------------------|--------|-------|-------|-----|--------|-------|------|----------|---------|------------|----|
| 09858 | LED2.5WB11E12/FIL/827-DIM-G7 | 200 | 2.5W | 2700K | 80+ | 120VAC | B11 | E12 | 3.8/96.6 | 1.38/35 | 15,000 | ★ |
| 09869 | LED2.5WT10/FIL/827-DIM-G7 | 250 | 2.5W | 2700K | 80+ | 120VAC | T10 | E26 | 5.31/135 | 1.3/33 | 15,000 | |
| 09866 | LED2.5WT6.5E17/FIL/827-DIM-G7 | 200 | 2.5W | 2700K | 80+ | 120VAC | T6.5 | E17 | 4.65/118 | 0.79/20 | 15,000 | |
| 09865 | LED2WT6E12/FIL/827-DIM-G7 | 120 | 2W | 2700K | 80+ | 120VAC | T6 | E12 | 3.15/80 | 0.71/18 | 15,000 | |
| 09856 | LED4.5WA15/FIL/827-DIM-G7 | 450 | 4.5W | 2700K | 80+ | 120VAC | A15 | E26 | 3.46/88 | 1.89/48 | 15,000 | |
| 09871 | LED4.5WA19/FIL/822-DIM-G7 | 350 | 4.5W | 2200K | 80+ | 120VAC | A19 | E26 | 3.94/100 | 2.36/60 | 15,000 | |
| 09857 | LED4.5WA19/FIL/SB/827-DIM-G7 | 400 | 4.5W | 2700K | 80+ | 120VAC | A19 | E26 | 3.94/100 | 2.36/60 | 15,000 | |
| 09859 | LED4.5WB11E12/FIL/827-DIM-G7 | 500 | 4.5W | 2700K | 80+ | 120VAC | B11 | E12 | 3.8/96.6 | 1.38/35 | 15,000 | |
| 09862 | LED4.5WG16/FIL/827-DIM-G7 | 500 | 4.5W | 2700K | 80+ | 120VAC | G16 | E26 | 3.15/80 | 2.17/55 | 15,000 | |
| 09875 | LED4.5WG25/FIL/827-DIM-G7 | 470 | 4.5W | 2700K | 80+ | 120VAC | G25 | E26 | | | 15,000 | |
| 09868 | LED4.5WT6.5E17/FIL/827-DIM-G7 | 450 | 4.5W | 2700K | 80+ | 120VAC | T6.5 | E17 | 4.65/118 | 0.79/20 | 15,000 | |
| 09855 | LED4WA15/FIL/827-DIM-G7 | 300 | 4W | 2700K | 80+ | 120VAC | A15 | E26 | 3.46/88 | 1.89/48 | 15,000 | |
| 09892 | LED4WB11E12/FIL/827-DIM-G7 | 300 | 4W | 2700K | 80+ | 120VAC | B11 | E12 | 3.8/96.6 | 1.38/35 | 15,000 | ★ |
| 09860 | LED4WBA11E12/FIL/827-DIM-G7 | 400 | 4W | 2700K | 80+ | 120VAC | BA11 | E12 | 4.84/123 | 1.38/35 | 15,000 | |
| 09861 | LED4WG16/FIL/827-DIM-G7 | 350 | 4W | 2700K | 80+ | 120VAC | G16 | E26 | 3.15/80 | 2.17/55 | 15,000 | |
| 09864 | LED4WS14/FIL/827-DIM-G7 | 300 | 4W | 2700K | 80+ | 120VAC | S14 | E26 | 3.19/81 | 1.77/45 | 15,000 | |
| 09863 | LED4WS14/FIL/822-DIM-G7 | 250 | 4W | 2200K | 80+ | 120VAC | S14 | E26 | 3.19/81 | 1.77/45 | 15,000 | |
| 09879 | LED4WST19/FIL/822K-DIM-G7 | 400 | 4W | 2200K | 80+ | 120VAC | ST19 | E26 | | | 15,000 | |
| 09870 | LED4WT10/FIL/827-DIM-G7 | 450 | 4W | 2700K | 80+ | 120VAC | T10 | E26 | 5.31/135 | 1.3/33 | 15,000 | |
| 09867 | LED4WT6.5E17/FIL/827-DIM-G7 | 300 | 4W | 2700K | 80+ | 120VAC | T6.5 | E17 | 4.65/118 | 0.79/20 | 15,000 | |
| 09878 | LED5WB11E26/FIL/827K-DIM-G7 | 500 | 5W | 2700K | 80+ | 120VAC | B11 | E26 | 3.62/92 | 1.38/35 | 15,000 | |
| 09877 | LED7WA19/FIL/827-DIM-G7 | 800 | 7W | 2700K | 80+ | 120VAC | A19 | E26 | 4.13/105 | 2.36/60 | 15,000 | ★ |
| 09441 | LED7WA19/FIL/SB/827K-DIM-G7 | 700 | 7W | 2700K | 80+ | 120VAC | A19 | E26 | 3.94/100 | 2.36/60 | 15,000 | |

NOTE: Use order code when ordering. ★ENERGY STAR® Approved

DIMENSIONS

