



HID Temporary Work Light

FEATURES

- 360° beam angle; 300° beam spread
- Base up, base down or horizontal operation
- Linkable for use in single outlet (60W = 10 pcs max; 100W = 6 pcs max; 150W = 4 pcs max)
- Provides easy operation and high lumen output with cage for protection in demanding environments
- Includes 6' power cord with plug and retractable handle
- M8 Screw Threads in lamp base for installation flexibility
- 5A overload protection
- Operates at 120V

WARRANTY

- 5 year limited warranty. Additional warranty options available. Contact EiKO for details

APPLICATIONS

- Task Lighting
- Commercial
- Work Areas
- Construction
- Temporary highbay

project name	type
catalog number	voltage
approved by	date



Linkable for use in single outlet

PERFORMANCE	Power Consumption	60W	100W	150W
	Lumens	7,200	12,000	18,000
	Efficacy (LPW)		120	
	Replace HID		150W	250W
	CRI		>80	
	Beam	360° angle; 300° spread		
	CCT	5000K		
	Life (L70)	50,000 hours		
	ELECTRICAL	Power Factor	≥0.9	
THD		>20%		
Input Voltage		120V		
CONSTRUCTION	Operating Temperature	-22°F to 140°F (-30°C to 60°C)		
	Base	Hook Base		
LISTINGS	Certification(s)	cULus Classified; FCC		
	Material Usage	RoHS Compliant; no mercury		
	Environment	IP64		



PERFORMANCE SUMMARY

ORDER CODE	ITEM #	LUMENS	WATTS	LPW	CCT	CRI	VOLTS	LIFE HOURS	REPLACES HID
11390	LED60WTMP50K-G8	7,200	60W	120	5000K	80+	120VAC	50,000	200W
11391	LED100WTMP50K-G8	12,000	100W	120	5000K	80+	120VAC	50,000	400W
11392	LED150WTMP50K-G8	18,000	150W	120	5000K	80+	120VAC	50,000	600W

PRODUCT DIMENSIONS

