

**shat-r-shield**<sup>®</sup> INC.



## Incoplas<sup>®</sup> LED Hybrid

The **Incoplas<sup>®</sup> LED Hybrid** fixture is a multi-purpose LED lighting solution that can be used as an area light, flood or wall pack.

- Specifically designed to withstand moisture, dust, chemicals, salt spray and harsh environments.
- Thermally Conductive Engineered Polymers that extract heat away from the light source and offer consistent heat dissipation.
- Significant weight reduction over comparable aluminum fixtures.

### **Specifications:**

- 45W/5,000 Lumens or 90W/10,000 Lumens
- 4,000K or 5,000K CCT
- 70 CRI
- Clear or Frosted Lens
- L70>60,000 Hours; Projected >100,000+ Hours
- Universal Driver 120-277V
- 0-10V Dimming
- Operating Temperature: -22°F to 113°F (-30°C to 45°C); Up to 122°F (50°C) in 5,000 lumen package
- Dimensions: 13"L x 10.25"W x 5.6"H
- Warranty: 5 year limited warranty
- Weight: 7.5 lbs. (3.4kg)




Buy America Compliant


[www.shatrshield.com](http://www.shatrshield.com)




## Beam Angles




15°  
Nema 3x3, Clear




17°  
Nema 3x3, Clear



28°  
Nema 4x4, Clear





113°  
Nema 7x7, Clear



116°  
Nema 7x7, Frosted

## Mounting Options



**Applications:** Marine Facilities, Industrial Facilities, Airports, Food Processing Plants, Cold Storage/Refrigeration, Wash Down Areas, Construction Sites, Tunnels, Livestock Farming, Wastewater Treatment Plants, Natatoriums

**Certifications** **DLC**, **cULus**, **NSF** Splash Zone, **IP66** Watertight & Dust-proof, **IP69K** High Temp & Pressure Jets, **NEMA4X** Watertight, **NEMA5** Dust-tight, **UL Wet Location**, **UL1598**, **UL1598A** Marine Grade, **ABS** Certified, **USDA** Approved; **HazLoc**: Class 1 Div 2, Groups A, B, C, D; Class 2 Div 2, Groups F, G; Class 3 Div 1 & 2