

### Features & Benefits

- Commercial Downlight Retrofit or New Construction
- Universal Voltage 120-277V
- UL for Safety, Wet-Location Rated
- Three Adjustable Lumen Output
- Three Adjustable CCT Options (3000K, 3500K, 4000K)
- Driver Efficiency Greater than 85% at full power
- THD ≤ 20% at full power
- High CRI
- Long Life
- Convenient and quick installation
- 0-10V Dimmable
- 25" Flexible Conduit
- Auto Recovery Short Circuit Protection, Over Load Protection, Over Voltage Protection
- Ambient Operating Temperature: -30 ~ 40°C
- Works in cold temperature applications
- Flicker-Free, Meets IEEE 1789-2015
- 5 Year Warranty



Commercial Recessed Downlight



### Specification Data

| Model No.         | Size      | IC Rated | Watts        | Lumens            | CCT                            | Efficacy | Input Voltage | CRI | Power Factor | Beam Angle (°) | Dimension                 |
|-------------------|-----------|----------|--------------|-------------------|--------------------------------|----------|---------------|-----|--------------|----------------|---------------------------|
| VEKR6D/8T/13W-10V | 6" Recess | Yes      | 6.5 / 9 / 13 | 790 / 1100 / 1560 | 3000K, 3500K, 4000K selectable | 120      | 120-277       | >80 | 0.9          | 100            | Dia. 8.27" x Height 4.25" |

### Ordering Information

Sample model: VEKR4D/8T/10W-10V

| VEKR                        | 4D           | 8T                      | 10W      | 10V           |
|-----------------------------|--------------|-------------------------|----------|---------------|
| Series                      | Size         | CRI>80                  | Wattage  | 0-10V dimming |
| Retrofit Kit Recessed Light | 4" Downlight | T: three CCT adjustable | 10W Max. |               |



User Manual

[468inDownlightInstallation.pdf](#)