

Features & Benefits

- Commercial Downlight Retrofit or New Construction
- Universal Voltage 120-277V
- UL for Safety, Wet-Location Rated
- Three Adjustable Lumen Output
- Three Adjustable CCT Options (3000K, 3500K, 4000K)
- Driver Efficiency Greater than 85% at full power
- THD ≤ 20% at full power
- High CRI
- Long Life
- Convenient and quick installation
- 0-10V Dimmable
- 25" Flexible Conduit
- Auto Recovery Short Circuit Protection, Over Load Protection, Over Voltage Protection
- Ambient Operating Temperature: -30 ~ 40°C
- Works in cold temperature applications
- Flicker-Free, Meets IEEE 1789-2015
- 5 Year Warranty



Commercial Recessed Downlight



Specification Data

Model No.	Size	IC Rated	Watts	Lumens	CCT	Efficacy	Input Voltage	CRI	Power Factor	Beam Angle (°)	Dimension
VEKR8D/8T/17W-10V	8" Recess	Yes	8.5 / 12 / 17	1030 / 1450 / 2040	3000K, 3500K, 4000K selectable	120	120-277	>80	0.9	100	Dia. 10.24" x Height 4.57"

Ordering Information

Sample model: VEKR4D/8T/10W-10V

VEKR	4D	8T	10W	10V
Series	Size	CRI>80	Wattage	0-10V dimming
Retrofit Kit Recessed Light	4" Downlight	T: three CCT adjustable	10W Max.	



User Manual

[468inDownlightInstallation.pdf](#)