

NT-5001

5" Baffle Splay Trim with Flange

Type _____

Project _____

Catalog No. _____

Notes _____

FEATURES

Trim: Precision spun high grade reflector and baffle with deep grooves to reduce aperture glare.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from plate within housing (if applicable), and mount socket in trim's neck.

COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

LAMP

Line Voltage

75W BR30/PAR30 (NH-501Q; NHIC-501QAT; NHR-504Q; NHRIC-504QAT)

GU24

26W GU24 (NHIC-5G24ATFL)

LABELS AND LISTINGS

· cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES AND DIMENSIONS



NT-5001B




NT-5001BZ



NT-5001N



NT-5001W



5" Baffle Splay Trim with Flange

Catalog No. _____

NT-5001B = Black Aluminum Baffle with White Flange

NT-5001BZ = Bronze Aluminum Baffle with Bronze Flange

NT-5001N = Natural Metal Aluminum Baffle Splay with Natural Metal Flange

NT-5001W = White Aluminum Baffle Splay with White Flange

Compatible Housings

Line Voltage

Catalog No. _____

NHIC-501QAT = 5" IC Air-Tight New Construction / 75W max

NHRIC-504QAT = 5" IC Air-Tight Remodel / 75W max

NH-501Q = 5" Non-IC New Construction / 75W max

NHR-504Q = 5" Non-IC Remodel / 75W max

GU24

Catalog No. _____

NHIC-5G24ATFL = 5" IC Air-Tight GU24 New Construction / 26W max

Example: **NT-5001B** = Black Aluminum Baffle with White Flange