



## WALL FIXTURE 169FM

## COMMERCIAL LIGHTING



SCAN FOR VIDEO



Wave Lighting's 169FM adds a modern look to any outdoor space. This fixture is ETL Listed and IP65 rated. The 169FM is double gasketed with a twist-lock lens for a water and bug-proof tight seal. Wave Lighting's 169FM is designed for wall or ceiling applications and mounting hardware is included.



### LED SOURCE OPTIONS

#### LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs L<sub>70</sub>
- Low Flicker (LT models)<sup>†</sup>
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT 80 or 90CRI
- 5 Year Warranty
- Energy Star


#### LED MULTI-VOLT SYSTEM - L22

- 120-277V, 50/60Hz
- Estimated 50,000 Hrs L<sub>70</sub>
- Max 20kA Surge Supression
- 4000K CCT 80CRI
- 5 Year Warranty

### SPECIFICATIONS

- Cast Aluminum Housing
- Mounting Hardware Included
- Black or White
- Frosted Polycarbonate Diffuser
- Wall Mount
- Minimum Starting Temp -20°F
- Hose Down - IP65 Rated
- ETL Listed for Wet Locations

BK BLACK WH WHITE



#### GUIDE: 169FMF-LR15C-BK

#### CALL FOR PHOTOMETRIC INFORMATION

ITEM #	DIFFUSER	LED LIGHT SOURCE	CCT	COLOR	OPTIONS
169FM	POLYCARBONATE F-Frosted	<b>120V LIGHTWAVE LED</b>	C-4K W-3K	BK-Black WH-White	EB-Emergency Backup O-Occupancy Sensor (options cannot be combined)  options are not available with LR32 & LT32 light source
		LR15-15W 1400lm 80CRI ★			
		LR22-23W 1900lm 80CRI ★			
		LR32-32W 2700lm 80CRI			
		LT15-16W 1400lm 90CRI			
		LT22-24W 2020lm 90CRI			
		LT32-32W 2700lm 90CRI			
		<b>120-277V MULTI-VOLT</b>	4K		
		L22-22W 1824lm			

† Lamp included. ★ Energy Star qualified product.