

**FL1001 FL1002 FL1003 FL1004 FL1005 UC8001**



**Under the Counter Light**

**Features**

**Housing**

Die-formed Cold-rolled Steel  
Low Profile, Suitable for Tight Space

**Optical**

Shade: Acrylic Diffuser

**Electrical**

120V

**Lamp**

CFL Type: F8T5, F13T5  
Linkable LED Type: More Color Temperature 3000K

**Certification**

UL/cUL, ETL/cETL Listed



**CFL Type**

Model	Input Voltage	Input Wattage	Lamp	LED CT	Shade	Dimension (L X W X H)
FL1001	120V	8W	F8T5, 8W	4100K	Acrylic	11.8" x 3.5" x 1.0"
FL1002	120V	13W	F13T5, 13W	4100K	Acrylic	21.3" x 3.5" x 1.0"
FL1003	120V	16W	F8T5, 8W x 2	4100K	Acrylic	24.5" x 3.5" x 1.0"
FL1004	120V	21W	F8T5,8W + F13T5,13W	4100K	Acrylic	33.1" x 3.5" x 1.0"
FL1005	120V	24W	F13T5, 13W x 2	4100K	Acrylic	42.5" x 3.5" x 1.0"

**Linkable LED Type**

Model	Input Voltage	Input Wattage	Lumen	LED CT	Shade	Dimension (L X W X H)
UC8001-12	120V	7.5W	320	4000K / 80	Acrylic	11.0" x 3.5" x 1.0"
UC8001-24	120V	11W	600	4000K / 80	Acrylic	24.0" x 3.5" x 1.0"
UC8001-33	120V	15W	820	4000K / 80	Acrylic	33.0" x 3.5" x 1.0"