



Specifications

Efficacy	120 LPW
Socket Type	E26, GU24, G24D-3 (diagonal 2-pin), GX23-2 (2-pin), G24Q (4-pin)
Color	2700K, 3000K, 3500K, 4000K, 5000K
CRI	> 80
Input Voltage	110V-277V
Operating Temp.	-20°F to 122°F
Wattage	6W, 11W
Beam Angle	360°

Ordering Information (G24D-3/GX23-2/G24Q)

Model #	Socket	Lumen	Wattage	Replace CFL Wattage	Color
APL-6-D-GX23-2-27K (G24D-3)	G24D-3	750lm	6W	13W	2700K
APL-6-D-GX23-2-30K (G24D-3)	G24D-3	750lm	6W	13W	3000K
APL-6-D-GX23-2-35K (G24D-3)	G24D-3	750lm	6W	13W	3500K
APL-6-D-GX23-2-40K (G24D-3)	G24D-3	750lm	6W	13W	4000K
APL-6-D-GX23-2-50K (G24D-3)	G24D-3	750lm	6W	13W	5000K
APL-6-D-GX23-2-27K	GX23-2	790lm	6W	13W	2700K
APL-6-D-GX23-2-30K	GX23-2	790lm	6W	13W	3000K
APL-6-D-GX23-2-35K	GX23-2	790lm	6W	13W	3500K
APL-6-D-GX23-2-40K	GX23-2	790lm	6W	13W	4000K
APL-6-D-GX23-2-50K	GX23-2	790lm	6W	13W	5000K
APL-11-D-GX23-2-27K	GX23-2	1240lm	11W	26W	2700K
APL-11-D-GX23-2-30K	GX23-2	1240lm	11W	26W	3000K
APL-11-D-GX23-2-35K	GX23-2	1240lm	11W	26W	3500K
APL-11-D-GX23-2-40K	GX23-2	1240lm	11W	26W	4000K
APL-11-D-GX23-2-50K	GX23-2	1240lm	11W	26W	5000K
APL-6-D-G24Q-27K	G24Q	790lm	6W	13W	2700K
APL-6-D-G24Q-30K	G24Q	790lm	6W	13W	3000K
APL-6-D-G24Q-35K	G24Q	790lm	6W	13W	3500K
APL-6-D-G24Q-40K	G24Q	790lm	6W	13W	4000K
APL-6-D-G24Q-50K	G24Q	790lm	6W	13W	5000K
APL-11-D-G24Q-27K	G24Q	1240lm	11W	26W	2700K
APL-11-D-G24Q-30K	G24Q	1240lm	11W	26W	3000K
APL-11-D-G24Q-35K	G24Q	1240lm	11W	26W	3500K
APL-11-D-G24Q-40K	G24Q	1240lm	11W	26W	4000K
APL-11-D-G24Q-50K	G24Q	1240lm	11W	26W	5000K

Features

- 50% energy saving and 75% maintenance reduction
- Cost-effective
- Rated for enclosed fixture
- GX23-2 & G24Q bases are dual-mode: ballast-compatible and line voltage friendly
- E26 & GU24 bases are line voltage friendly
- Can be installed horizontally or vertically with the same beam spread as traditional lamps
- 5-year warranty / Rated 50,000 hours lifetime

Product Compliance & Certifications:

- UL and cUL Type A/Type B listed (OOLV/OOLV7.E479597)
- UL and cUL classified (IFAR/IFAR7.E325073)

Description

Aleddra's LED PL Replacement Lamp offers the first 360-degree LED PL lamp with 100 lm/w efficacy. Unlike other LED PL lamps on the market today, this revolutionary lamp can be installed either vertically or horizontally with the same beam spread as traditional lamps.

Size:

6W: 1 3/8"W x 1 3/8"L x 4.5"H
(top to socket edge, not including the in-socket length)

11W: 1 3/8"W x 1 3/8"L x 6.1"H
(top to socket edge, not including the in-socket length)

Ordering Information (E26/GU24)

Model #	Socket	Lumen	Wattage	Replace CFL Wattage	Color
APL-6-A-E26-27K	E26	790lm	6W	13W	2700K
APL-6-A-E26-30K	E26	790lm	6W	13W	3000K
APL-6-A-E26-35K	E26	790lm	6W	13W	3500K
APL-6-A-E26-40K	E26	790lm	6W	13W	4000K
APL-6-A-E26-50K	E26	790lm	6W	13W	5000K
APL-11-A-E26-27K	E26	1240lm	11W	26W	2700K
APL-11-A-E26-30K	E26	1240lm	11W	26W	3000K
APL-11-A-E26-35K	E26	1240lm	11W	26W	3500K
APL-11-A-E26-40K	E26	1240lm	11W	26W	4000K
APL-11-A-E26-50K	E26	1240lm	11W	26W	5000K
APL-6-A-GU24-27K	GU24	790lm	6W	13W	2700K
APL-6-A-GU24-30K	GU24	790lm	6W	13W	3000K
APL-6-A-GU24-35K	GU24	790lm	6W	13W	3500K
APL-6-A-GU24-40K	GU24	790lm	6W	13W	4000K
APL-6-A-GU24-50K	GU24	790lm	6W	13W	5000K
APL-11-A-GU24-27K	GU24	1240lm	11W	26W	2700K
APL-11-A-GU24-30K	GU24	1240lm	11W	26W	3000K
APL-11-A-GU24-35K	GU24	1240lm	11W	26W	3500K
APL-11-A-GU24-40K	GU24	1240lm	11W	26W	4000K
APL-11-A-GU24-50K	GU24	1240lm	11W	26W	5000K

* The 6W PL lamp should be used with no higher than a 13W ballast.

* The 11W PL lamp should be used with no higher than a 26W ballast.

* This lamp cannot be used with emergency ballast.