





- Easily switch between 3000K, 3500K, 4000K, 5000K or 6500K CCT on the unit with FlexCOLOR.
- Hybrid driver allows installation with compatible instant start ballasts* or 120-277VAC line voltage.
- Can be installed as single or double-ended power.
- 10W, 11W, 12W & 15W models available.
- Available in 2 FT, 3 FT & 4 FT.
- Uniform illumination from our glass construction.
- Frosted glass lens softens the light output.
- Approved for use in enclosed fixtures.

FLEXCOLOR SWITCH BETWEEN 5 CCTS


DIMENSIONS



LED-10T8-FCAB24-G4




LED-11T8-FCAB36-G4



LED-12T8-FCAB48-G4 / LED-15T8-FCAB48-G4

EMERGENCY LIGHTING OPTIONS (AVAILABLE SEPARATELY)



WORKS W/ LED-EMG-05WCP AND LED-EMG-10WCP



CRI

LIGHT DISTRIBUTION

BALLAST BYPASS OR COMPATIBLE

SINGLE OR DOUBLE-ENDED

LED-FCA MODELS

BEAM ANGLE

50,000hrs RATED LIFE

PART #	UPC	REPLACES	WATTAGE	LUMENS	CCT	BASE	DIMENSIONS	DLC CODE
LED-10T8-FCAB24-G4	197810005988	17W	10W	1450	FLEXCOLOR 3000K/3500K/ 4000K/5000K/ 6500K	G13	24.0" x 1.0"	S-7MG7GF
LED-11T8-FCAB36-G4	197810005995	25W	11W	1650			36.0" x 1.0"	S-RDX5L5
LED-12T8-FCAB48-G4	197810006008	32W	12W	1800			48.0" x 1.0"	S-6GRHYK
LED-15T8-FCAB48-G4	197810006015		15W	2200				S-J0PGVS

DEFAULT CCT FOR FLEXCOLOR IS SHOWN IN BOLD.

** OR COMPATIBLE ELECTRONIC BALLAST.

* LAMP IS COMPATIBLE WITH CERTAIN INSTANT START BALLASTS. PLEASE VERIFY COMPATIBILITY PRIOR TO INSTALLATION.

