



# AL SERIES

# THE ALL PACK

The AL Series is a configurable area light with multiple applications. It can be configured as a dark-sky compliant, forward throw, or pole-mounted light.



Intertek



75,000 to LIFETIME

100,000 HRS



includes labor allowance





## CONSTRUCTION & COMPATIBILITY

- Heavy duty LEDs
- Patented, reversible two-part design
- Two optic distribution options
- Metallic reflector for maximum light output
- "Hands-free" wiring with knockouts on back & sides
- Available standard in durable bronze and white powder coat
- Compatible with 0-10V dimming controls
- Compatible with many photocells & motion sensors
- When combined with AL series slipfitter, compatible with all Jarvis pole-mounting tenons, bullhorns, and brackets



Ask your Jarvis Lighting representative about pole mounting options!

## OPTICS & MOUNTING DIAGRAM



## ELECTRICAL & LIGHT OUTPUT SPECIFICATIONS

MODEL	# LEDS	INPUT	POWER	LUMENS	CCT	CRI	PF	OPTICS
AL-100	1	120-277V 50/60 Hz	29W	3,182 lm	5000K	>70	>.9	W OR F
AL-250	2		60W	6,354 lm				
AL-320	3		77W	8,403 lm				
AL-400	4		105W	11,780 lm				W ONLY

## ORDERING CHART

### PRODUCT FAMILY

**AL** SERIES:  
ALL PACK

### METAL HALIDE EQUIVALENT

**100** (100W equivalent, 29W)  
**250** (250W equivalent, 60W)  
**320** (320W equivalent, 77W)  
**400** (400W equivalent, 105W)

### LED OPTICS

**W** (wide/angled)  
**F** (flood/direct)

### FINISH

**BRZ** (bronze)  
**WHT** (white)



**JARVIS**  
**LIGHTING**