



GE
Lighting

34279 - Integrated 4ft LED Glass Tubes

LED10ET8/G/4/835

- ☞ Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall.
- ☞ Each LED tube is outfitted with an internal GE driver.
- ☞ The GE integrated LED tubes run on electronic T8 instant-start or programmed start ballasts.
- ☞ 2.3x longer life than LFL (70,000 vs. 30,000 hours)
- ☞ No UV
- ☞ Easy disposal, non-hazardous waste
- ☞ UL Listed
- ☞ DLC rated
- ☞ Check ballast compatibility at www.gelighting.com/LEDTUBES-ballast-compatibility

Product Photo



GENERAL CHARACTERISTICS

| | |
|-------------------------|------------|
| Base Description | LED_Bs_G13 |
| Base Type | G13 |
| Dimmable | No |
| Product Technology | LED |
| Rated Life (Hours) | 70000 h |
| Dimmable / Non-Dimmable | No |

PHOTOMETRIC CHARACTERISTICS

| | |
|---------------------------|---------|
| Initial Lumens-nominal | 1600 lm |
| Color Rendering Index-CRI | 80 |
| Color Temperature | 3500 K |

PRODUCT INFORMATION

| | |
|----------------------------------|------------------|
| Product Code | 34279 |
| Description | LED10ET8/G/4/835 |
| Alternative Unit Of Measure | EACH |
| Standard Package Quantity | 20 |
| Ean UPC | 0043168342797 |
| Standard Package GTIN | 00043168342797 |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard Package | 20 |
| Sales Unit | Each |
| UCC | |
| Alternative Unit Of Measure | CASE |
| Standard Package Quantity | 20 |
| Ean UPC | 043168342797 |
| Standard Package GTIN | 10043168342794 |
| No Of Items Per Sales Unit | |
| No Of Items Per Standard Package | 20 |
| Sales Unit | Case |
| UCC | |

DIMENSIONS

| | |
|-----------------------------|---------|
| Bulb Max Overall Length-MOL | 48.0 in |
|-----------------------------|---------|

ELECTRICAL CHARACTERISTICS

| | |
|---------------------|------|
| Rated power (Watts) | 10 W |
|---------------------|------|