



GE  
Lighting

## 95854 - GE LED RS Cans

### LED10RS4/830E26P 120

- ☞ GE LED RS Can Downlights are the perfect refit solution to give an updated look to ceilings with recessed lighting. Simply replace the existing BR30 lamp with the LED downlight, no tools or wiring required.
- ☞ For example, using only 8 watts of energy, saves over \$44 in energy costs over the rated life of a lamp vs. a standard 65 watt incandescent lamp based on \$0.11 per kWh and provides similar light output (700 vs 755 lumens)
- ☞ Better fit with reduced MOL for shallower cans
- ☞ 4" Can. Pigtail Attachment
- ☞ Energy Star Rated

### Product Photo



### CAUTIONS & WARNINGS

#### Caution

Risk of Electric Shock

Suitable for damp locations

Not intended for use with emergency exit fixtures or emergency exit lights

Performance may vary with electronic timers / photocells or dimmers

Use in totally enclosed fixtures may result in lower lamp life

### GENERAL CHARACTERISTICS

Base Description	LED_Bs_E26
Base Type	E26
Dimmable	Yes
Product Technology	LED
Rated Life (Hours)	50000 h
Dimmable / Non-Dimmable	Yes
10 Digit U	4316895854
Lamp Count	1
Life in Years	45.7 yr
Requested Structure	Carton
Estimated Energy Cost per Year	1.2

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens-nominal	700 lm
Color Rendering Index-CRI	80
Color Temperature	3000 K

### PRODUCT INFORMATION

Product Code	95854
Description	LED10RS4/830E26P 120
Alternative Unit Of Measure	EACH
Standard Package Quantity	12
Ean UPC	043168958547
Standard Package GTIN	00043168958547
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
Sales Unit	Each
UCC	043168958547
Alternative Unit Of Measure	CASE
Standard Package Quantity	12
Ean UPC	043168958547
Standard Package GTIN	10043168958544
No Of Items Per Sales Unit	12
No Of Items Per Standard Package	12
Sales Unit	Case
UCC	043168958547

### DIMENSIONS

Bulb Max Overall Length-MOL	4.32 in
-----------------------------	---------

### ELECTRICAL CHARACTERISTICS

Voltage <Nom>	120 V
Input Voltage [nom]	120 V
Rated power (Watts)	10 W