naturaled®

Turning Light into Savings

CCM
Canopy Ceiling Mount





Optical Lens
Precise Beam Control

40W, 60W

Our CCM series brings you our square shape surface mount with polycarbonate lens with excellent thermal design. Die cast aluminum housing, uniform and consistent color, DLC listed. CCM is ideal for any locations wall or ceiling mount.

CCM are used in damp locations such as canopies, covered walkways, entrance eaves, stairwells, parking, etc.

5 YEAR WARRANTY

BEAM ANGLE 140°

50,000 Rated Life Hours

Key Features & Benefits

- DesignLights Consortium Certified
- Long Life LED Chips
- Uniform and consistent color
- Excellent thermal design
- 15-30 foot height performance
- Universal Voltage 120-277V
- Operating Temp: -22°F~122°F
- 50,000 hrs rated average life

Applications

- Area Lighting
- Security Lighting
- Pathway Lighting
- Perimeter Lighting
- Entryway Lighting
- Parking Garage

Color Choices

White Bronze

Qualifications

IP65 outdoor rated · DLC · cULus · FC · LM 79 · LM 80 · RoHS COMPLIANT


2000 S. Grove Ave, Bldg B, Ontario, CA 91761 | tel: 909-930-6868 fax: 909-930-9988 | www.mynaturaLED.com

© 2016 Plusrite®

ORDERING INFORMATION


Item Code	Description	Color Temp	Wattage	Lumen Output	Equivalent Wattage	Voltage (V)	CRI	Beam Angle	Rated Hours	Color	DLC	IP65
7166	LED-FXCCM40/40K/DB	4000K	40	3,429	175	120-277	82	140°	50,000	Bronze	•	•
7167	LED-FXCCM40/50K/DB	5000K	40	3,429	175	120-277	82	140°	50,000	Bronze	•	•
7538	LED-FXCCM40/40K/WH	4000K	40	3,429	175	120-277	82	140°	50,000	White	•	•
7539	LED-FXCCM40/50K/WH	5000K	40	3,429	175	120-277	82	140°	50,000	White	•	•
7084	LED-FXCCM60/40K/DB	4000K	60	5,258	250	120-277	81	140°	50,000	Bronze	•	•
7085	LED-FXCCM60/50K/DB	5000K	60	4,948	250	120-277	81	140°	50,000	Bronze	•	•
7537	LED-FXCCM60/50K/WH	5000K	60	4,948	250	120-277	81	140°	50,000	White	•	•


Dimensions





Wattage	A	B	C	Weight (lbs)
40W	9.00-in	9.00-in	8.00-in	4.70
60W	12.50-in	12.50-in	9.00-in	7.72

Illuminace Distribution










Master Carton Package



Package (Master)
1