

ULTRA LED™ HO PAR Lamps



Key Features & Benefits

- Sleek, lightweight design
- Up to 100 LPW
- Long life: up to 25,000 hours (L₇₀)
- 15°, 25° and 40° beam option
- 120 or universal (120-277) voltage options
- Outstanding color uniformity and beam quality utilizing COB technology
- 277V option allows compatible replacement for HID lamps
- UL1993 & UL1598C tested
- PAR30/PAR38 – UL Wet rated
- High CBCP performance
- Great replacement options for high power halogen and HID lamp
- Rated for use in enclosed fixtures

ULTRA LED HO PAR lamps deliver exceptionally high lumen output along with outstanding color uniformity and beam quality utilizing COB technology. Offered in a smooth heat sink, these lamps are available in a 15° spot, 25° narrow flood and 40° flood with the option of 120 or universal (120-277) voltage. The high CBCP performance makes these lamps a great replacement for high power halogen and HID lamps.

Product Offering

Ordering Abbreviation	Wattage	Beam Angle	Color Temperature
LED PAR30LN	19, 25	15°, 25°	3000K
LED PAR38	25, 26, 30	15°, 25°, 40°	3000K & 5000K

Application Information

Market Segments

- Grocery
- Houses of worship
- Manufacturing
- Retail
- Warehouse/storage

Application Notes

1. Operating temperature -4°F to 104°F (-20°C to 40°C).
2. Use in fixtures that support a half pound lamp.
3. Not for use with emergency light fixtures or exit lights.
4. Can be used in enclosed fixtures (lamp life may be affected).
5. Suitable for wet locations.

Applications

- Downlights
- General lighting
- Spotlights

Specifications and Certifications



Specification Data

Catalog #	Type
Project	
Comments	
Prepared by	

Ordering Information

Item Number	Ordering Abbreviation	Wattage (W)	Base Type	Replaces	Beam Angle	Input Voltage (V)	CBCP	Average Rate Life (L70)	Dimmable	CCT	CRI	Typical Lumens	Power Factor	ENERGY STAR®
79361	LED19PAR30LN/HO/DIM/830/SP15/W/120	19	Medium	75W Halogen*	15°	120	17,600	25,000	Yes	3000K	81	1800	0.99	Yes
79362	LED19PAR30LN/HO/830/SP15/W/UNV	19	Medium	75W Halogen*	15°	120-277	17,600	25,000	No	3000K	81	1800	0.99	Yes
79693	LED25PAR30LN/HO/830/NFL25/W/UNV	25	Medium	75W Halogen*	25°	120-277	10,000	25,000	No	3000K	81	2300	0.99	Yes
79363	LED26PAR38/HO/DIM/830/SP15/W/120	26	Medium	150W Halogen	15°	120	20,000	25,000	Yes	3000K	81	2400	0.99	Yes
79364**	LED26PAR38/HO/830/SP15/W/UNV	26	Medium	150W Halogen	15°	120-277	20,000	25,000	No	3000K	81	2400	0.99	Yes
74795	LED25PAR38/HO/830/SP15/W/UNV	25	Medium	150W Halogen	15°	120-277	20,000	25,000	Yes	3000K	82	2500	0.95	Yes
74085**	LED26PAR38/HO/DIM/830/FL40/W	26	Medium	250W Halogen	40°	120	4500	25,000	Yes	3000K	82	2400	0.99	Yes
74796	LED25PAR38/HO/DIM/830/FL40/W	25	Medium	250W Halogen	40°	120	4500	25,000	Yes	3000K	82	2650	0.95	Yes
79479**	LED26PAR38/HO/DIM/850/FL40/W/RP	26	Medium	250W Halogen	40°	120	4500	25,000	Yes	5000K	82	2400	0.99	Yes
74794	LED25PAR38/HO/DIM/850/FL40/W/RP	25	Medium	250W Halogen	40°	120	4500	25,000	Yes	5000K	82	2650	0.95	Yes
79600	LED30PAR38/HO/830/NFL25/W/UNV	30	Medium	250W Halogen	25°	120-277	14,000	25,000	No	3000K	82	3000	0.99	Yes

*Based on max wattage equivalency allowed by ENERGY STAR. CBCP is similar to 120W halogen lamp.


**79364 is being phased out and 74795 is replacing it, 74085 is being phased out and 74796 is replacing it, 79479 is being phased out and 74794 is replacing it.

Ordering Guide

LED	25	PAR38	/	HO	/	DIM	/	8	30	/	SP	15	/	W	/	UNV
LED Lamps and Retrofits	Wattage: 19, 25, 26, 30	Lamp Type: PAR38 PAR30LN		High Output		Dimmable		CRI = 81	Color Temperature 3000K		Spot	Beam Angle 15°		Wet Rated		120-277V

Lamp Dimensions

	MOL (inches)	Diameter (inches)
19W LED PAR30LN	4.48 in	3.77 in
25W LED PAR30LN	4.6 in	3.74 in
25W LED PAR38	5.07 in	4.72 in
30W LED PAR38	5.1 in	4.8 in



Dimensions Inches (mm)

Energy Savings

Basic Product Description	LED Life (hrs.)	Similar Halogen	Halogen Life (hrs.)	Watts Saved	Energy Savings*	LED Life vs. Incandescent
LED 30W PAR38	25,000	70W HID/250W Halogen	2,500	220	\$605.00	10X
LED 26W PAR38	25,000	250W	2,500	224	\$616.00	10X
LED 26W PAR38	25,000	150W	2,500	124	\$341.00	10X
LED 19W PAR30LN	25,000	120W	2,500	101	\$277.75	10X
LED 25W PAR30LN	25,000	39W HID/75W Halogen	2,500	50	\$137.50	10X

* Energy savings over the life of the lamp calculated at \$0.11/kWh

LEDVANCE LLC
 200 Ballardvale Street
 Wilmington, MA 01887 USA
 Phone 1-800-LIGHTBULB (1-800-544-4828)
 www.sylvania.com

SYLVANIA and LEDVANCE are registered trademarks.
 All other trademarks are those of their respective owners.
 Licensee of product trademark SYLVANIA in general lighting.
 Specifications subject to change without notice.

[/sylvania](#) [/sylvania](#)

