



Energetic Lighting's E2WPC series is the creative contemporary redesign of the wall mounted security light. Ideal for use where LED commercial wall pack fixtures provide a quick and easy solution for multi-family, residential, and apartment applications. Available in 10W and 20W, designed to replace traditional 100W equivalent incandescent wall pack fixtures. An integrated dusk-to-dawn photocell sensor automatically turns the fixture on/off relative to ambient light.

### Features

- No UV or IR radiation
- Modern and efficient design
- Integrated dusk-to-dawn sensor
- Suitable for wet location use
- Easy and secure installation
- Various color finishes
- 0-10 dimming

### Applications

- Commercial canopy locations
- Covered walkways
- Overhead task lighting
- General lighting

### Specification

Order Number	70045	70046	70047	70051	70025
Model Number	E2WPC10L-730	E2WPC10L-750	E2WPC20L-730	E2WPC20L-750WH	E2WPC20L-750
Configuration	with Photocell	with Photocell	with Photocell	with Photocell	with Photocell
Body Color/Finish	Dark Brown	Dark Brown	Dark Brown	White	Dark Brown
Lumen Output	1100 LM	1100 LM	2200 LM	2200 LM	2200 LM
Luminous Efficacy	110 LM/W	110 LM/W	110 LM/W	110 LM/W	110 LM/W
Input Power	10 W	10 W	20 W	20 W	20 W
Input Voltage	120-277 Vac	120-277 Vac	120-277 Vac	120-277 Vac	120-277 Vac
Power Factor	>0.9	>0.9	>0.9	>0.9	>0.9
THD	<0.2	<0.2	<0.2	<0.2	<0.2
Color Temp (CCT)	3000 K	5000 K	3000 K	3000 K	5000 K
Color Rend (CRI)	>70	>70	>70	>70	>70
Lifetime Rating	50000 hours	50000 hours	50000 hours	50000 hours	50000 hours
Warranty	5 Years	5 Years	5 Years	5 Years	5 Years
Dimmability	0-10v	0-10v	0-10v	0-10v	0-10v
Operating Temp	-40 to 104 (°F)	-40 to 104 (°F)	-40 to 104 (°F)	-40 to 104 (°F)	-40 to 104 (°F)
Environment	Wet Location	Wet Location	Wet Location	Wet Location	Wet Location
DLC			DLC Standard		DLC Standard
Safety Cert	UL	UL	UL	UL	UL
Weight	2 LBS	2 LBS	2 LBS	2 LBS	2 LBS
Dimensions	9.9"x5.6"x3.2"	9.9"x5.6"x3.2"	9.9"x5.6"x3.2"	9.9"x5.6"x3.2"	9.9"x5.6"x3.2"