



Energetic Lighting's LED Strip Light family of fixtures are designed to emulate the look of traditional fluorescent T8 tube lights. This series offers variations from 10W up to 40W outputs, and single and double strip appearances. 0-10V dimming and 120-277VAC operation are featured. Designed for series installation, the easy end connection design facilitates any install. Combining a durable stells housing, rugged polymer diffuser, and an L70 lifetime of 50,000 hours will provide many years of dependable and worry free use.

Features

- 0-10v dimmable
- No UV or IR radiation
- Minimalistic and efficient design
- Mercury-free construction
- Suitable for Damp Location use
- Toolless wire compartment entry
- Linkable ends with included adapter

Applications

- Architectural decor
- Overhead task lighting
- Limited space mounting locations
- General lighting

Specification

Order Number	30032	30029
Model Number	E3SLA20D4-840	E3SLA40D4-840
Configuration	Single	Double
Beam Angle	130°	130°
Lumen Output	2174 LM	4305 LM
Luminous Efficacy	110 LM/W	110 LM/W
Input Power	20 W	39 W
Input Voltage	120-277 Vac	120-277 Vac
Power Factor	0.9	0.9
THD	0.15	0.15
Color Temp (CCT)	4000 K	4000 K
Color Rend (CRI)	80	80
Lifetime Rating	50000 hours	50000 hours
Warranty	5 Years	5 Years
Dimmability	0-10v	0-10v
Operating Temp	-4 to 122 (°F)	-4 to 122 (°F)
Environment	Damp Location	Damp Location
DLC	DLC Standard	DLC Standard
Safety Cert	UL	UL
Weight	3 LBS	5.2 LBS
Dimensions	48.2"x1.8"x2.2"	48.2"x3.5"x2.2"