



Features

- Constant voltage non-dimming plug-in driver
- Available in 12V and 24V options
- Wattages ranging from 40W up to 96W
- 6ft 18AWG power cord with 3-prong plug
- 5ft 18AWG tail with male DC jack
- cULus Listed (dry locations)

Wattage/Voltage Options

- 40W (12V / 24V)
- 60W (24V)
- 90W (24V)
- 96W (12V)

2-wire DC Adapter Accessory (DC-VPI)



2-wire DC Adapter Accessory (DC-HW)



Listing / Ratings



PS Plug-in Driver - 12V / 24V

Use one of these five constant voltage DC power supplies for non-dimming plug-in applications, based on the capacity and voltage needed. The DC-HW accessory can be used with Trulux tape light, ideally with a switched outlet since the driver does not include an inline switch. Use the DC-VPI for powering low voltage products with bare leads, such as LightStar reels. cULus Listed for use in dry locations.

Technical Information

Series	PS Plug-in 12V / 24V
Max Load	See ordering information
Minimum Load	N/A
Input Voltage	120V AC
Output Voltage	12V DC / 24V DC
Dimmable	N/A
Input Wire	6ft 18AWG power cord + 3-prong plug
Output Wire	5ft 18AWG tail with male DC jack
Rating	cULus Listed (dry locations)
Dimensions	5-3/4"L x 2"W x 1-1/4"H (40W) 6-3/4"L x 2-3/8"W x 1-1/4"H (90W / 96W)

Ordering Information

PS-40-12VPI	PS Plug-in 12V - 40W Driver
PS-96-12VPI	PS Plug-in 12V - 96W Driver
PS-40-24VPI	PS Plug-in 24V - 40W Driver
PS-60-24VPI	PS Plug-in 24V - 60W Driver
PS-90-24VPI	PS Plug-in 24V - 90W Driver
DC-VPI	2-wire DC adapter cable - Bare wire to Female DC
DC-HW	2-wire DC adapter cable - Bare wire to Male DC